

## CONDITIONS FOR ACCEPTANCE

# Asbestos waste, brittle or unbound

|                   |                |
|-------------------|----------------|
| <b>EURAL code</b> | <b>170601*</b> |
| <b>Waste code</b> | <b>042002</b>  |

### DESCRIPTION

Brittle or unbound asbestos waste, such as plaster insulation, sprayed asbestos, soft asbestos plates, rope seal, asbestos felt or cardboard and badly weathered asbestos cement

### ADDITIONAL CONDITIONS

#### General conditions:

- No radioactive material
- No other hazardous waste
- No roofing, asphalt, or construction materials containing significant amounts of bituminous binder

#### Packaging conditions:

- The asbestos waste is tightly sealed and double-walled in sturdy UN-approved bags or big bags, labeled with the ADR label (Class 9) and asbestos logo, with the following text: "a, asbestos, caution contains asbestos, inhaling asbestos dust is harmful to health, comply with safety regulations."
- Asbestos waste can be delivered in PE bags. These must be properly sealed, double-walled, sufficiently strong, tear-resistant, and labeled with the asbestos logo. Woven bags are not permitted. The maximum weight is 25 kg. The maximum dimensions of the bags are 1100 mm x 630 mm.
- Asbestos waste that can be cemented can also be delivered in big bags. These must meet the following criteria:
  - Maximum dimensions: 90 x 90 x 125 cm
  - Safety closure at the top
  - Flat bottom
  - Fully double-walled (PP-coated fabric)
  - Airtightly sealed
  - Asbestos logo on at least 2 sides
  - UN-approved
  - Maximum weight: 1000 kg
  - Equipped with 4 loops for unloading with a forklift

Lightly contaminated waste that is compressible (such as plastic waste, filters, overalls, gloves, fibrous insulation material, etc.) is not allowed in big bags. These materials must always be packed in double transparent PE bags.

- **Larger items**, such as pipes, ovens, doors, and metal pieces, can be delivered in other packaging, with prior written approval, provided they meet at least the following criteria:
  - Airtight and double-walled packaging with asbestos logo
  - On a pallet with the large items secured to the pallet
  -
- Asbestos waste that does not meet the specified packaging requirements must be repacked. An additional cost will be charged for this.