

## CONDITIONS FOR ACCEPTANCE

# Mixed rubble

### DESCRIPTION

All stone and concrete-like materials, whether or not reinforced, other than stone mesh, plaster and/or asphalt.

Maximum dimension 60 x 60 x 60 cm.

### Permitted

- Concrete (residues) and paving stones <100 v%
- Bricks, masonry, or concrete rubble <100 v%
- Reinforcing steel, rebar
- (Clean) sand <5 v%

### Prohibited

- Hazardous waste
- Powders and dusty waste
- Cement
- Liquid concrete (concrete may not be poured in liquid form into a container)
- Sand-lime brick
- Gypsum products; aerated concrete; Gibo blocks
- Asphalt and/or asphalt rubble
- Plasterwork
- Contaminated soil categorised less than residential soil quality
- Decontaminated soil
- Residues from municipal solid waste incineration
- Immobilized waste
- Materials removed from IBC constructions
- Metallurgical slag, not meeting the conditions for use in hydraulic recycling granulate
- Non-ferrous slag from the non-ferrous industry;
- Rubble and concrete waste originating from suspect contaminated locations as petrol stations, car dismantling sites, remediation sites
- Asbestos or suspect asbestos-containing materials
- Paper, foil and plastics
- Batteries and car batteries

*\* If, upon delivery, deviations are found from the described conditions, Renewi Nederland B.V. reserves the right to refuse the consignment in question or to accept it according to amended conditions.*

*\*\* Your obligation and opportunity to separate can be found in the National Waste Management Plan (LAP)*