

CONDITIONS FOR ACCEPTANCE

Construction and demolition waste

DESCRIPTION

Recyclable waste generated during the construction, demolition and/or renovation of buildings.
The percentage of recyclable waste is at least 70 v%.

Permitted

- Mix of rubble: bricks, masonry, paving stones, concrete and concrete residues <100 v%
- Rigid plastics
- Solid and non-impregnated wood such as: hardboard, softboard, engineered wood, laminate, chipboard, fibreboard, composite wood and hardwood
- Ferrous and non-ferrous metals
- Paper and cardboard
- Construction foil <30 v%
- Flooring such as carpet, linoleum and PVC <10v%
- Insulation materials such as mineral wool, fibreglass, EPS (polystyrene), wood wool cement board <5 v%
- Glass <2 v%
- Gypsum, gypsum blocks and aerated concrete <5 v%

Prohibited

- Hazardous (chemical) waste such as paint cans, sealant cartridges, PUR canisters, etc.
- Asbestos or suspect asbestos-containing materials (e.g. Eternit, New Technology roofing sheet)
- Batteries and car batteries
- Pressurized cylinders such as fire extinguishers, gas bottles, etc.
- Burnt waste
- Burning or smouldering waste
- Roofing waste, roofing materials
- Sleepers, impregnated wood, wood from waterworks and foundations, wood that has been in the water for a long time
- Rubble from chimneys, soot
- Agricultural foil
- Tyres, rubber and technical rubber
- Soil
- Municipal waste (bulky) and bin bags
- Mattresses and sofas
- Powders and dusty waste
- Organic waste such as pruning waste, garden waste and food waste
- Substances causing odour nuisance
- White and brown goods, such as refrigerators, solar panels and other electrical apparatus

** If, upon delivery, deviations are found from the described conditions, Renewi Nederland B.V. reserves the right to refuse the consignment in question or to accept it according to amended conditions.*

*** Your obligation and opportunity to separate can be found in the Circular Materials Plan (CMP)*