

CONDITIONS FOR ACCEPTANCE

Concrete rubble

DESCRIPTION

Concrete rubble from construction and demolition activities.

Permitted

Only materials containing concrete from construction, renovation and demolition without contamination, except for reinforcement present in concrete rubble. For example, concrete rubble with or without reinforcement, cured residual concrete and masonry mortar. In case of contamination exceeding 10 v%, the offered load will be accepted as construction and demolition waste.

Maximum dimension 60 x 60 cm

Prohibited

- Hazardous waste
- Construction and demolition waste
- Commercial waste
- Clean rubble
- Sand-lime brick
- Gypsum products; aerated concrete; Gibo blocks
- Asphalt and/or asphalt rubble
- Plasterwork
- Sand/soil >5 v%
- Contaminated sand/soil, decontaminated soil
- Rubble from chimneys
- Roof gravel
- Asbestos or suspect asbestos-containing materials
- Residues from municipal solid waste incineration
- Immobilized waste
- Materials removed from IBC constructions
- Metallurgical slag, not meeting the conditions for use in hydraulic recycling granulate
- Non-ferrous slag from the non-ferrous industry;
- Rubble and concrete waste originating from suspect contaminated locations as petrol stations, car dismantling sites, remediation sites

** If, upon delivery, deviations are found from the described conditions, Renewi Nederland B.V. reserves the right to refuse the consignment in question or to accept it according to amended conditions.*

*** Your obligation and opportunity to separate can be found in the Circular Materials Plan (CMP)*